



国家 3C 认证



ISO9000



美国 DOT 认证



青岛宏驰轮胎有限公司
QINGDAO HONGCHI TYRE CO.,LTD.

青岛恒达轮胎有限公司
QINGDAO HENGDA TYRE CO.,LTD.



青岛宏驰轮胎有限公司
QINGDAO HONGCHI TYRE CO.,LTD.

青岛恒达轮胎有限公司
QINGDAO HENGDA TYRE CO.,LTD.

出口部地址：中国青岛开发区长江中路 230 号国际贸易中心 A1503

Export Dept:A1503,International Trade Center,No.230 Changjiang Middle Road,Qingdao,China

电话 (TEL):0086-532-68972391 传真 (FAX) :0086-532-68972391,86312666

邮箱 (EMAIL):admin@hengdatyre.com

网站 (WEBSITE):www.hengdatyre.com www.hongchityre.com

工厂地址：山东省青岛平度前楼工业园

Factory:Qian Lou Rubber Industrial Park,Pingdu,Qingdao,China

电话 (TEL):0086-532-86313006 86313888 传真 (FAX):0086-532-86312666

HONGCHI® HENGTA® FOREVER®

PROFESSIONAL TYRE MANUFACTURER SINCE 1994





企业简介

COMPANY PROFILES

青島恒達輪胎有限公司始建於 1994 年，是一家集工程機械輪胎、工業車輛輪胎、農業裝備輪胎、輕卡載重輪胎、港機輪胎、林業輪胎、礦山輪胎、特種輪胎生產於一體的综合型進出口生產企業，已有二十多年的生產經驗。公司於 2017 年被宏馳輪胎廠收購。目前公司綜合生產能力為輪胎 200 萬套，其中自營出口 5000 萬美元。

公司已通過 CCC 國家強制性認證，ISO9000 國際質量體系認證，美國 DOT 認證，為公司在市場立足與業務拓展奠定了堅實的基础。其輪胎品牌“HENGSTAR”、“FOREVER”、“HONGCHI”產品在國內暢銷 20 多個省、市、自治區，國際市場遠銷歐洲、中東、北美、東南亞、澳洲、非洲等國家和地區，深受廣大客戶歡迎。

公司自成立以來始終堅持“以人為本，誠信立足”的經驗原則，堅持“質量第一，客戶至上”的服務理念，倡導“科技創新，誠信經營”企業文化，與時俱進，以“誠信、質量”服務市場，使企業和產品贏得了廣大客戶的長久信賴。真誠希望與更多的國內外客戶建立長期的合作關係，共創美好未來。我們熱烈歡迎新老客戶來我司洽談業務。

QINGDAO HENGDA TYRE CO.,LTD. Is one of the major tyre manufacturers in China which was established in 1994.Our company is a comprehensive enterprise, with import, export and manufacturing of OTR tyres, Industrial Tyres, Agricultural Tyres, Truck tyres, Mining Tyres, Port machinery tyres, and special sized tyres, Has more than 20 years of production experience.The company was acquired by Hong Chi tire factory in 2017. At present, the company's comprehensive production capacity is 2 million sets of tires, of which self-exports are 50 million US dollars.

Our company successfully passed the national CCC compulsory certification, ISO9000 international quality management system certification and USA DOT certification, which laid a solid foundation for expansion. The company tire brand "HENGSTAR", "FOREVER", "HONGCHI" products have been sold to more than 20 provinces, cities and autonomous regions in China, the international market include Europe, the Middle East, North America, Southeast Asia, Australia, Africa and other countries and regions.

Our business principle is People-oriented and Honesty. We believe that the sincerity is uppermost and client is first. We will serve our customers based on Honesty and High Quality Products. We will always achieve the best for you! Sincerely hope to build good and long-term cooperation with more and more domestic and foreign friends!

厂房设备

PLANT AND EQUIPMENT



证书资质

CERTIFICATES



产品目录

PRODUCT CONTENTS

OFF-THE-ROAD TYRE 工程机械轮胎	07-09
REACH STACKER(PORT USE) TYRE 港口工业轮胎	10
AGRICULTURAL TYRE (INCLUDE IRRIGATION TYRE) 农业胎 (包含灌溉胎系列)	11-17
INDUSTRIAL TYRE 工业胎	18-22
PNEUMATIC FORKLIFT TYRE 叉车胎	23-24
SOLID TYRE 实心胎	24
TRUCK TYRE 卡车胎	25-31

TRAILER TYRE 拖车胎	32
AGRICULTURAL IMPLEMENT TYRE 农机具轮胎	33
MILITARY TYRE 军用胎	33
SAND TYRE 沙漠胎	34
FLOATION TYRE 浮力胎	34
FOREST SPECIAL SIZED TYRE 林业异形胎	35
GRASS MACHINERY TYRE 草地机械轮胎	36
SELF-MADE MOLD 自制模具	36

E-3/L-3 A



规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
7.50-16	8PR	E-3/L-3A	6.00G	810	215	250	650
8.25-16	10PR	E-3/L-3A	6.50H	885	235	280	970
9.00-16	10PR	E-3/L-3A	6.50H	834	225	310	1080
9.00-20	14PR	E-3/L-3A	7.0	1018	259	810	2500
10.00-16	12PR	E-3/L-3A	W8L	910	275	310	1090
11.00-16	12PR	E-3/L-3A	W10L	884	244	320	1100
12.00-16	12PR	E-3/L-3A	8.5	884	244	320	1100
14/90-16	12PR	E-3/L-3A	8.5	896	215	290	1245
16/70-16	14PR	E-3/L-3A	8.5H	870	260	390	1055
16/90-16	14PR	E-3/L-3A	8.5H	870	260	390	1055
16/70-20	16PR	E-3/L-3A	13.00	1075	410	350	3375
16/70-24	16PR	E-3/L-3A	13.00	1175	410	450	3350
20.5/70-16	14PR	E-3/L-3A	8.5H	1075	410	350	2850
23.5/70-16	14PR	E-3/L-3A	8.5H	1075	410	350	2850
15.5-25	16PR	E-3/L-3A	12.00/1.3	1275	395	225	6750
17.5-25	16PR	E-3/L-3A	14.00/1.5	1350	445	475	7300
17.5-25	20PR	E-3/L-3A	14.00/1.5	1350	445	575	8250
20.5-25	20PR	E-3/L-3A	17.00/2.0	1490	520	450	9500
20.5-25	24PR	E-3/L-3A	17.00/2.0	1490	520	525	10300
23.5-25	20PR	E-3/L-3A	19.50/2.5	1615	595	375	10900
23.5-25	24PR	E-3/L-3A	19.50/2.5	1615	595	475	12500
23.5-25	28PR	E-3/L-3A	19.50/2.5	1615	595	550	13600
26.5-25	24PR	E-3/L-3A	22.00/3.0	1750	675	400	14000
26.5-25	28PR	E-3/L-3A	22.00/3.0	1750	675	475	15500
26.5-25	32PR	E-3/L-3A	22.00/3.0	1750	675	550	17000
29.5-25	28PR	E-3/L-3A	25.00/3.5	1875	750	425	17500
29.5-25	32PR	E-3/L-3A	25.00/3.5	1875	750	475	18800
29.5-29	32PR	E-3/L-3A	25.00/3.5	1975	750	500	19000
29.5-29	40PR	E-3/L-3A	25.00/3.5	1975	750	625	23600
13.00-24	12PR	E-3/L-3A	10.00W	1301	351	450	3875
14.00-20	24PR	E-3/L-3A	10.00W	1245	375	890	8500
14.00-24	16PR	E-3/L-3A	10.00W	1370	375	550	7300
14.00-24	20PR	E-3/L-3A	10.00W	1370	375	700	8500
14.00-24	24PR	E-3/L-3A	10.00W	1370	375	850	9500
14.00-24	28PR	E-3/L-3A	10.00W	1370	375	925	10000
14.00-25	24PR	E-3/L-3A	10.00/1.5	1370	375	850	9500
14.00-25	28PR	E-3/L-3A	10.00/1.5	1370	375	925	10000
14.00-25	32PR	E-3/L-3A	10.00/1.5	1370	375	950	10375
16.00-24	24PR	E-3/L-3A	11.25/2.0	1495	430	650	10600
16.00-24	28PR	E-3/L-3A	11.25/2.0	1495	430	750	11500
16.00-25	28PR	E-3/L-3A	11.25/2.0	1495	430	750	11500
16.00-25	32PR	E-3/L-3A	11.25/2.0	1495	430	875	12500
18.00-24	32PR	E-3/L-3A	13.00/25	1615	500	750	15000
18.00-25	32PR	E-3/L-3A	13.00/25	1615	500	750	15000

E-3/L-3 B

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
20.5/70-16	14PR	E-3/L-3B	8.5H	1075	410	350	2850
17.5-25	16PR	E-3/L-3B	14.00/1.5	1350	445	475	7300
17.5-25	20PR	E-3/L-3B	14.00/1.5	1350	445	575	8250
20.5-25	20PR	E-3/L-3B	17.00/2.0	1490	520	450	9500
20.5-25	24PR	E-3/L-3B	17.00/2.0	1490	520	525	10300
23.5-25	20PR	E-3/L-3B	19.50/2.5	1615	595	375	10900
23.5-25	24PR	E-3/L-3B	19.50/2.5	1615	595	475	12500
23.5-25	28PR	E-3/L-3B	19.50/2.5	1615	595	550	13600
26.5-25	24PR	E-3/L-3B	22.00/3.0	1750	675	400	14000
26.5-25	28PR	E-3/L-3B	22.00/3.0	1750	675	475	15500
26.5-25	32PR	E-3/L-3B	22.00/3.0	1750	675	550	17000



E-3/L-3 NEW

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
9.00-16	10PR	E-3/L-3 NEW	6.50H	834	225	310	1080
20.5/70-16	14PR	E-3/L-3 NEW	8.5H	1075	410	350	2850
23.5/70-16	14PR	E-3/L-3 NEW	8.5H	1075	410	350	2850

L-5

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
17.5-25	20PR	L-5	14.00/1.5	1400	445	575	8250
20.5-25	20PR	L-5	17.00/2.0	1550	520	525	10300
23.5-25	20PR	L-5	19.50/2.5	1675	595	475	12500
26.5-25	20PR	L-5	22.00/3.00	1800	675	475	15500



工程机械轮胎

OFF-THE-ROAD TYRE

R-3

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
23.1-26	10PR	R-3	DW20	1500	595	1400	2900



G-2/L-2



规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
15.5-25	16PR	G-2/L-2	12.00/1.3	1275	395	525	6500
17.5-25	16PR	G-2/L-2	14.00/1.5	1330	410	275	3350
17.5-25	20PR	G-2/L-2	14.00/1.5	1330	410	325	3650
20.5-25	16PR	G-2/L-2	17.00/2.0	1490	575	225	4000
20.5-25	20PR	G-2/L-2	17.00/2.0	1490	575	275	4500
23.5-25	20PR	G-2/L-2	19.50/2.5	1615	595	250	5450
13.00-24	12PR	G-2/L-2	8.00TG	335	1280	300	2725
13.00-24	16PR	G-2/L-2	8.00TG	335	1280	400	3200
14.00-24	12PR	G-2/L-2	8.00TG	360	1350	325	3450
14.00-24	16PR	G-2/L-2	8.00TG	360	1350	375	3650
16.00-24	12PR	G-2/L-2	10.00VA	470	1460	225	3650
16.00-24	16PR	G-2/L-2	10.00VA	470	1460	325	4500

G-2/L-2 半实心耐刺扎

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
16/70-20	14PR	G-2/L-2	13 SDC	1070	410	450	5150
16/70-24	14PR	G-2/L-2	13 SDC	1175	410	450	5600
20.5/70-16	16PR	G-2/L-2	8.5H	950	400	350	2850



G-2/L-2 EXCAVATOR

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
9.00-20	16PR	G-2/L-2	7	1038	259	825	4750
10.00-20	16PR	G-2/L-2	7.5	1073	278	810	3000

REACH STACKER (PORT USE) TYRE

港口工业轮胎

L-5S

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
12.00-24	28PR	L-5S	8.5	1245	315	825	6900
14.00-24	28PR	L-5S	10.00	1370	375	925	10000
18.00-25	40PR	L-5S	13.00/2.5	1671	495	950	17000
18.00-25	48PR	L-5S	13.00/2.5	1671	495	1100	27600



E-4/H548

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
12.00-24	28PR	E-4 H548	8.5	1245	315	950	9900
14.00-24	36PR	E-4 H548	10.00	1370	375	925	10000
26.5-25	40PR	E-4 H548	22.00/3.0	1800	675	625	18000
18.00-25	40PR	E-4 H548	13.00/2.5	1671	495	950	17000
18.00-25	48PR	E-4 H548	13.00/2.5	1671	495	1100	27600

E-4/H538-S

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
14.00-24	36PR	E-4/H538-S	10.00	1370	375	925	10000
18.00-25	40PR	E-4 H538-S	13.00/2.5	1671	495	950	17000
18.00-25	48PR	E-4 H538-S	13.00/2.5	1671	495	1100	27600



E-3/L-3 A

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 10Km/H	单胎负荷 (kg) MAX LOADING 10km/H
26.5-25	40PR	E-3/L-3A	22.00/3.0	1800	675	550	17000
16.00-25	36PR	E-3/L-3A	11.25/2.0	1495	430	1150	18400
18.00-25	40PR	E-3/L-3A	13.00/2.5	1671	495	950	17000



R-1 SERIAL 1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
5.00-12	6PR	R1-1	4.00E	590	145	200	280
5.50-17	10PR	R1-1	4.00E	735	150	280	400
6.00-12	6PR	R1-1	4.50E	640	165	250	405
6.00-14	6PR	R1-1	4.50E	690	165	250	450
6.00-16	8PR	R1-1	4.50E	745	165	250	495
6.50-16	8PR	R1-1	5.00F	760	180	250	565
7.00-16	8PR	R1					
7.50-16	8PR	R1-1	5.00F	810	205	210	650
7.50-20	8PR	R1-1	5.00F	910	205	210	760
8.3-20	6PR	R1-1	W7	895	210	240	695
8.3-24	8PR	R1-1	W7	995	210	240	810
8.5-20	8PR	R1-1	W7	895	210	230	705
9.5-20	8PR	R1-1	W8	950	240	280	955
9.5-24	8PR	R1-1	W8	1050	240	280	1076
9.5-28	8PR	R1-1	W8	1140	240	280	1185
9.5-32	8PR	R1-1	W8	1250	240	280	1260
10.00-15	8PR	R1-1	9.0*15.3	855	276	240	1425
10/75-15.3	10PR	R1-1	9.0	760	264	390	1090
11-32	10PR	R1-1	W10	1360	305	140	1000
11-38	10PR	R1-1	W10	1540	305	160	1545
11.2-24	10PR	R1-3	W10	1105	285	180	1045
11.2-28	10PR	R1-1	W10	1205	285	240	1305
11.2-38	10PR	R1-1	W10	1459	285	120	1055
12-38	10PR	R1-1	DW11	1575	330	220	1800
12.4-24	10PR	R1-2	W11	1160	315	230	1415
12.4-28	10PR	R1-2	W11	1260	315	1510	230
13.6-24	10PR	R1-3	W12	1210	345	250	1790
13.6-28	10PR	R1-3	W12	1310	345	250	1910
13.6-38	10PR	R1-2	W12	1565	345	250	2215
14.9-24	10PR	R1-3	W13	1265	378	230	1990
14.9-26	10PR	R1-2	W13	1315	378	230	2055
14.9-28	10PR	R1-2	W13	1365	378	230	2120
14.9-30	10PR	R1-2	W13	1415	378	230	2190
15.5/80-24	10PR	R1-2	W13	1240	394	300	2900
15.5-38	10PR	R1-3	W14L	1570	395	230	2320
16.9-24	10PR	R1-2	W15L	1335	430	200	2230
16.9-28	10PR	R1-2	W15L	1435	430	200	2380
16.9-30	10PR	R1-2	W15L	1485	430	200	2455
16.9-34	10PR	R1-2	W15L	1585	430	200	2605
16.9-38	10PR	R1-2	W15L	1685	430	200	2760
18.4-26	12PR	R1-2	DW16	1450	467	230	2985
18.4-30	12PR	R1-2	W16L	1550	467	180	2815
18.4-34	12PR	R1-2	W16L	1655	467	230	3375
18.4-38	12PR	R1-2	W16L	1755	467	230	3575
20.8-38	10PR	R1-2	W18L	1835	528	160	3475
23.1-26	12PR	R1-2	DW20	1605	587	170	3610



R1-1



R1-2



R1-3

R-1 SERIAL 2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
12.4-48	12PR	R-1S	W11	1802	305	320	3850
12.4-54	12PR	R-1	W11	1972	315	320	4000
15-24	10PR	R1-4	DW14	1310	400	280	2800
15L-24	14PR	R1-5	DW14	1146	345	280	2110



R-1 STRENGTHEN PATTERN

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
12.4-28	10PR	R-1	W11	1260	315	230	1510
13.6-28	10PR	R-1	W12	1310	345	250	1910
14.9-28	10PR	R-1	W13	1365	378	230	2120



R-1 SERRIED PATTERN

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
23.1-26	12PR	R-1	DW20	1605	587	170	3610
23.1-30	12PR	R-1	DW20	1705	587	170	3865





R-2 SERIAL 1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
18.4-30	12PR	R-2	W16L	1550	467	180	2815
18.4-34	12PR	R-2	W16L	1655	467	230	3375
19.5L-24	12PR	R-2	DW16	1367	495	210	2145
23.1-26	12PR	R-2	DW20	1605	587	170	3610
23.1-30	12PR	R-2	DW20	1705	587	170	3865

R-2 SERIAL 2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
14.9-24	10PR	R-2 NEW	W13	1265	378	230	1990
14.9-28	10PR	R-2 NEW	W13	1365	378	230	2120



R-2 SERIAL 3

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
28L-26	12PR	R-2	DW25	1620	805	170	4245

R-2 SERIAL 4

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
19.5L-24	12PR	R-2	DW16	1367	495	210	2145



R-2 SERIAL 5

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
5.00-12	6PR	R-2	4.00E	590	145	200	280
6-14	6PR	R-2	5.00	650	154	200	395
7-16	6PR	R-2	6.00	750	183	200	405
8.3-20	6PR	R-2	W7	895	210	240	695
8.3-22	6PR	R-2	W7	945	210	270	970
8.3-24	8PR	R-2	W7	995	210	240	810
9.5-22	8PR	M2	W8	1000	240	270	1135
11.2-24	10PR	R-2	W10	1105	285	180	1045
11-32 水旱两用	8PR	R-2	W10	1393	303	210	1320
8-16	6PR	M1	6.0	790	211	195	617
8-18	6PR	M1	6.0	841	211	240	650
12.4-24	10PR	M3	W11	1160	315	230	1415
13.6-26	12PR	M2	W12	1260	345	250	1790



R-2



M1



M2



M3



F-2 SERIAL 1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
4.00-12	6PR	F-2 2RIB	3.00D	535	110	330	300
4.00-14	6PR	F-2 2RIB	3.00D	590	110	380	350
4.00-16	6PR	F-2 2RIB	3.00D	640	110	380	380
4.50-16	6PR	F-2 2RIB	3.00D	655	120	400	610
5.00-15	6PR	F-2 2RIB	4J	665	140	470	500
5.50-16	6PR	F-2 2RIB	4.00E	710	150	370	525
6.00-16	6PR	F-2 2RIB	4.00E	740	160	340	560
6.50-16	8PR	F-2 2RIB	4.50E	760	175	420	640
7.50-16	8PR	F-2 2RIB	5.50F	810	205	370	870
7.50-18	8PR	F-2 2RIB	5.50F	860	205	370	945
7.50-20	8PR	F-2 2RIB	5.50F	910	205	370	1020
10.00-16	8PR	F-2 2RIB	W8L	894	274	390	1280
10.00-16	8PR	F-2 3RIB	W8L	894	274	390	1280
11.00-16	8PR	F-2 2RIB	W10L	967	315	345	1350
11.00-16	8PR	F-2 3RIB	W10L	967	315	345	1350



F-2 2RIB



F-2 3RIB

F-2 SERIAL 2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.50-20	8PR	F-2 NEW	5.00F	860	180	420	865
7.50-20	8PR	F-2 NEW	5.50F	910	205	370	1020



PR-1 PADDY FIELD TYRE

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.00-12	6PR	PR-1	4.50E	640	165	250	405
6.00-14	6PR	PR-1	4.50E	690	165	250	450
6.50-16	8PR	PR-1	5.00F	760	180	250	565
7.50-16	8PR	PR-1	5.00F	810	205	210	650
8.3-20	6PR	PR-1	W7	895	210	240	695
8.3-24	8PR	PR-1	W7	995	210	240	810
9.00-20	8PR	PR-1	W8	1034	228	210	750
9.5-20	8PR	PR-1	W8	1050	240	240	1140
9.5-24	8PR	PR-1	W8	1150	240	310	1420
11.2-24	10PR	PR-1	W10	1205	285	310	1800
11-32	10PR	PR-1	W10	1460	305	160	1080
12.4-28	10PR	PR-1	W11	1315	315	200	1785
13.6-38	10PR	PR-1	W12	1710	345	250	2780
14.9-30	10PR	PR-1	W13	1560	378	210	2200
16.9-34	10PR	PR-1	W15L	1687	430	220	3385



R-1 Off-Road Pattern

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
10/75-15.3	12PR	R-1 CROSS	9.0	760	264	310	1800



IRRIGATION TYRE 灌溉胎系列

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
14.9-24	10PR	SERIAL 1	W10	1265	378	230	1600
11.2-38	10PR	SERIAL 2	W10	1459	285	230	1150
11.2-38	10PR	SERIAL 3	W10	1459	285	230	1150



SERIAL 1



SERIAL 2



SERIAL 3

I-1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
*5.90-15	4PR	I-1	4.5	657.9	157.5	250	515
*6.70-15	6PR	I-1	4.5	703.6	167.6	300	730
*7.60-15	8PR	I-1	5.5	721.4	200.7	360	950
*9.5L-14	8PR	I-1	8.00	741	241	300	1090
9.5L-15	8PR	I-1	8LB	767	241	300	1120
10-15	8PR	I-1	8L13	855	276	240	1425
11L-14	8PR	I-1	8KB	752	279	250	1100
11L-15	8PR	I-1	W8L	777	279	250	1150
11L-16	8PR	I-1	8.00	798	274	250	1215
12.5L-15	8PR	I-1	10.00	823	318	250	1360



IMP100/IMP-101

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.00-12	12PR	IMP-100	5.00	683	192	390	1050
10.0/80-12	8PR	IMP-100	9.00	710	264	390	1250
10.0/75-15.3	10PR	IMP-100	9.00	760	264	390	1525
11.5/80-15.3	10PR	IMP-100	9.00	865	290	410	2145
12.5/80-15.3	10PR	IMP-100	9.00	875	307	510	2810
12.5/80-18	12PR	IMP-101	9.00	965	307	370	2650

R-1 INDUSTRIAL TYRE SERIAL 1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
405/70-20 (16/70-20)	14PR	R-1 NEW	13.0	1100	395	350	3250
405/70-24 (16/70-24)	14PR	R-1 NEW	13.0	1200	410	400	3550



R-1 INDUSTRIAL TYRE SERIAL 2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
405/70-20 (16/70-20)	14PR	R-1 M880	13.0	1076	407	350	3250
405/70-24 (16/70-24)	14PR	R-1 M880	13.0	1178	407	350	3550

R-1 INDUSTRIAL TYRE SERIAL 3

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
405/70-20 (16/70-20)	14PR	R-1 M600	13.0	1076	407	350	3250
405/70-24 (16/70-24)	14PR	R-1 M600	13.0	1178	407	350	3550
20.5/70-16	14PR	R-1 M600	W11	865	310	390	1600
23.5/70-16	14PR	R-1 M600	W11	910	335	390	1600



工业胎

INDUSTRIAL TYRE

R-4

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
10.5/80-18	10PR	R4-3	W9	875	279	370	1935
12.5/80-18	12PR	R4-3	11.0	1001	350	370	2625
16.9-24	12PR	R4-2	15	1236	429	260	3250
16.9-28	12PR	R4-1	15	1435	430	260	3450
17.5L-24	10PR	R4-4	15	1241	445	190	1900
18.4-26	12PR	R4-1	16	1450	467	250	3075
18.4-26	12PR	R4-2	16	1450	467	230	2985
19.5L-24	12PR	R4-2	17	1314	495	230	3455
19.5L-24	12PR	R4-4	17	1314	495	230	3455
21L-24	12PR	R4-4	18	1402	533	250	3075



R4-1



R4-2



R4-3



R4-4

SKS-1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
9.00-16	12PR	SKS-1	6.5			520	3035
10-16.5	10PR	SKS-1	8.25	779	261	520	2170
11L-16	12PR	SKS-1	8.00	838	279	440	1250
12-16.5	12PR	SKS-1	9.75	790	300	550	2900
14-17.5	14PR	SKS-1	10.5	922	351	550	3875
15-19.5	14PR	SKS-1	11.75	1029	391	485	4565



INDUSTRIAL TYRE

工业胎

SKS-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
10-16.5	10PR	SKS-2	8.25	779	261	520	2170
12-16.5	12PR	SKS-2	9.75	790	300	550	2900



SKS-3

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
10-16.5	10PR	SKS-3	8.25	779	261	520	2170
12-16.5	12PR	SKS-3	9.75	790	300	550	2900

SKS-4

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
10-16.5	10PR	SKS-4	8.25	779	261	520	2170
12-16.5	12PR	SKS-4	9.75	790	300	550	2900



SKS-5

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
5.70-12	6PR	SKS-5	4.5	647	146	420	660
15.5/60-18	10PR	SKS-5	8.25	779	261	520	2170
23x8.5-12	6PR	SKS-5	7.00	574	213	340	820
27x8.5-15	6PR	SKS-5	7.00	678	213	350	1030
27x10.5-15	6PR	SKS-5	8.5	691	259	340	1090



AT117

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
9.00-16	14PR	AT117	6.50	880	225	360	1500



F-3

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
11L-15	10PR	F-3	8.00	813	279	360	1060
11L-16	14PR	F-3	8.00	838	279	420	1250



G-2/L-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE 40Km/H	单胎负荷 (kg) MAX LOADING 40km/H
12.5/70-16	16PR	G-2/L-2	12.00/1.3	1275	395	525	6500
15.5/60-18	16PR	G-2/L-2	14.00/1.5	1330	410	275	3350



L-5 SKID STEER TYRE--SERIAL 1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
10-16.5	10PR	L5-1	8.25	779	261	520	2170
12-16.5	12PR	L5-1	9.75	790	300	550	2900
12.5/80-18	16PR	L5-1	W9	965	306	480	4055
10-16.5	10PR	L5-2	8.25	779	261	520	2170
12-16.5	12PR	L5-2	9.75	790	300	550	2900
12.5/80-18	16PR	L5-2	W9	965	306	480	4055



L5-1



L5-2

L-5 SKID STEER TYRE--SERIAL 2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
19.5L-24	12PR	L5-1 NEW	17.00	1340	495	230	3455
19.5L-24	12PR	L5-2 NEW	17.00	1340	495	230	3455



L5-1 NEW



L5-2 NEW

叉车胎

PNEUMATIC FORKLIFT TYRE

H818

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
3.00-15	16PR	H818	8.00	840	300	900	6825
5.00-8	10PR	H818	3.50D	470	137	900	1295
6.00-9	10PR	H818	4.00E	540	160	850	1795
6.50-10	10PR	H818	5.00F	590	175	775	1965
7.00-9	10PR	H818	5.00F	590	190	860	1995
7.00-15	12PR	H818	5.50F	750	200	945	3100
7.50-15	12PR	H818	6.00G	750	200	945	3100
7.00-12	14PR	H818	5.00S	683	192	1000	2670
18*7-15	14PR	H818	4.33R	465	173	900	1840
21*8-19	14PR	H818	6.00E	535	200	900	2300
23*10-12	12PR	H818	8.00	632	200	700	3290
23*9-10	16PR	H818	7.00	584	229	800	2300
250-15	16PR	H818	7.5	735	250	850	4350
27*10-12	14PR	H818	8.00G	690	250	750	3620
8.15-15(28*9-15)	14PR	H818	7.00	710	220	800	3285
8.25-12	12PR	H818	6.5	765	235	720	3060
8.25-15	14PR	H818	7	840	235	830	3775



H818-S

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.50-16	16PR	H818-S	6.00G	805	215	1030	5440



H838

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
5.00-8	10PR	H838	3.50D	470	137	900	1295
6.00-9	10PR	H838	4.00E	540	160	850	1795
6.50-10	10PR	H838	5.00F	590	175	775	1965
7.00-9	10PR	H838	5.00F	590	190	860	1995
7.00-12	14PR	H838	5.00S	683	192	1000	2670
8.15-15(28*9-15)	14PR	H838	7.00	710	220	800	3285
8.25-15	14PR	H838	7	840	235	830	3775



PNEUMATIC FORKLIFT TYRE

叉车胎

H669

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
9.00-20	14PR	H669	7.00	1038	259	760	5195
10.00-20	16PR	H669	7	1073	278	790	6030
12.00-20	18PR	H669	8.5	1145	315	790	7155



SOLID TYRE

实心胎

HD101

规格 SIZE	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	单胎负荷 (kg) MAX LOADING
4.00-8	HD101	3.00	400	111	730
5.00-8	HD101	3.00	455	125	840
200/50-10	HD101	6.50	441	187	1630
6.00-9	HD101	4.00	515	143	1325
6.50-10	HD101	5.00	566	153	1820
7.00-9	HD101	5.00	536	157	1785
7.00-12	HD101	5.00	643	176	2075
7.00-15	HD101	5.50	711	187	2475
7.50-16	HD101	5.5/6.0/6.5	787	187	2700
8.15-15(28*9-15)	HD101	7.00	691	208	2820
8.25-12	HD101	5.00	696	189	3010
8.25-15	HD101	6.50	810	204	3045
8.25-20	HD101	6.5/7.0	933	212	3475
900-16	HD101	6.50	844	216	3550
900-20	HD101	6.5/7.0	948	222	4450
10.00-20	HD101	7.5/8.0	1038	264	5010
11.00-20	HD101	7.5/8.0	1038	264	5010
12.00-20	HD101	8.0/8.5	1086	282	5959
21*8-9	HD101	6.00	505	192	1940
15*4-1/2-8	HD101	3.00	370	109	625
16*6-8	HD101	4.33	404	147	1035
18*7-8	HD101	4.33	440	155	1620
23*9-10	HD101	6.50	561	191	2765
23*10-12	HD101	8.00	586	227	2980
27*10-12	HD101	8.00	661	232	3080
250-15	HD101	7.50	693	228	3010
300-15	HD101	8.00	788	238	4130



RIB TRUCK TYRE PATTERN 曲线花纹系列卡车胎

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
*4.50-12	8PR	RIB	3.00B	545	105	550	535
*5.00-12	8PR	RIB	3.50B	568	143	462	487
*5.50-13	8PR	RIB	4.00B	620	160	500	560
*5.90-13	6PR	RIB					
*6.00-13	8PR	RIB	4.50B	655	170	420	580
*6.00-14	8PR	RIB	41/2J	680	170	420	600
*6.00-15	8PR	RIB	4.50E	705	170	420	630
6.50-14	10PR	RIB	41/2J	705	180	530	690
6.50-15	10PR	RIB	4.50E	730	180	420	825
6.50-16	10PR	RIB	5.50F	750	185	530	860
7.00-15	12PR	RIB	5.50F	750	200	630	1080
7.00-16	12PR	RIB	5.50F	775	200	630	965
7.50-15	12PR	RIB	6.00G	780	215	730	1285
7.50-16	12PR	RIB	6.00G	805	215	770	1320
8.25-16	14PR	RIB	6.50H	855	235	730	1705
7.50-20	14PR	RIB/LUG	6.0	935	215	810	1900
8.25-20	16PR	RIB/LUG	6.5	974	236	910	2430
9.00-20	16PR	RIB/LUG	7.0	1018	259	880	2900
10.00-20	16PR	RIB/LUG	7.5	1073	278	795	3000
11.00-20	18PR	RIB/LUG	8.0	1105	293	910	3650
12.00-20	18PR	RIB/LUG	8.5	1145	315	795	3725
12.00-24	18PR	RIB/LUG	8.5	1247	315	810	4250
11.00-20	18PR	M-777	8.0	1105	293	910	3650



LUG TRUCK TYRE PATTERN 羊角花纹系列卡车胎

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
*5.50-13	8PR	LUG	4.00B	620	160	500	560
*6.00-13	8PR	LUG	4.50B	655	170	420	580
*6.00-14	8PR	LUG	41/2J	680	170	420	600
*6.00-15	8PR	LUG	4.50E	705	170	420	630
6.00-16	10PR	LUG	4.50E	730	170	530	755
6.50-14	10PR	LUG	41/2J	705	180	530	690
6.50-16	10PR	LUG	5.50F	750	185	530	860
7.00-15	12PR	LUG	5.50F	750	200	630	1080
7.00-16	12PR	LUG	5.50F	775	200	630	965
7.50-15	12PR	LUG	6.00G	780	215	730	1285
7.50-16	12PR	LUG	6.00G	805	215	770	1320
8.25-16	14PR	LUG	6.50H	855	235	730	1705
7.50-20	14PR	RIB/LUG	6.0	935	215	810	1900
8.25-20	16PR	RIB/LUG	6.5	974	236	910	2430
9.00-20	16PR	RIB/LUG	7.0	1018	259	880	2900
10.00-20	16PR	RIB/LUG	7.5	1073	278	795	3000
11.00-20	18PR	RIB/LUG	8.0	1105	293	910	3650
12.00-20	18PR	RIB/LUG	8.5	1145	315	795	3725
12.00-24	18PR	RIB/LUG	8.5	1247	315	810	4250
11.00-20	18PR	M-777	8.0	1105	293	910	3650



EXTRA SUPER RIB

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.00-15	12PR	EXTRA SUPER RIB	5.50F	750	200	630	1080
7.00-16	12PR	EXTRA SUPER RIB	5.50F	775	200	630	965
7.50-15	12PR	EXTRA SUPER RIB	6.00G	780	215	730	1285
7.50-16	12PR	EXTRA SUPER RIB	6.00G	805	215	770	1320
8.25-16	14PR	EXTRA SUPER RIB	6.50H	855	235	730	1705

EXTRA SUPER LUG

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.00-15	12PR	EXTRA SUPER LUG	5.50F	750	200	630	1080
7.00-16	12PR	EXTRA SUPER LUG	5.50F	775	200	630	965
7.50-15	12PR	EXTRA SUPER LUG	6.00G	780	215	730	1285
7.50-16	12PR	EXTRA SUPER LUG	6.00G	805	215	770	1320
8.25-16	14PR	EXTRA SUPER LUG	6.50H	855	235	730	1705



卡车胎

TRUCK TYRE

GRASS MACHINERY TYRE

卡车胎

LUG-R

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.50-16	12PR	EXTRA SUPER LUG-R	6.00G	805	215	770	1320



SS1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.50-16	12PR	SS1	6.00G	805	215	770	1320

MT-777

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
*6.00-14	8PR	MT-777	41/2J	680	170	420	600



SUPER LUG 78

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.50-16	12PR	SUPER LUG 78	6.00G	805	215	770	1320

LUG

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.50-16	16PR	LUG	6.00G	805	215	770	1320



LUG XL

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
4.50/5.00-12	12PR	LUG XL	3.50B	568	143	462	487
6.50-14	10PR	LUG XL	41/2J	705	180	530	690

M-777

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
11.00-20	18PR	M-777	8.0	1105	293	910	3650



SQ1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
8.25-16	16PR	SQ1	6.50H	815	175	770	1850
12.00-24	18PR	SQ1	8.5	1247	315	810	4250

LUG H101

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.50-16	12PR	LUG H101	6.00G	805	215	770	1320



RIB H201

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.50-16	12PR	RIB H201	6.00G	805	215	770	1320

H661

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.00-13	10PR	H661	4.50E	655	170	530	670
6.00-14	10PR	H661	4.50J	665	125	530	800
6.00-15	10PR	H661	4.50E	695	120	530	825
6.00-16	10PR	H661	4.50B	730	170	530	750



H665

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.50-16	14PR	H665	5.50F	740	140	630	1040
7.00-16	14PR	H665	5.50F	770	145	770	1330
7.50-16	14PR	H665	6.00G	805	160	770	1550

H666

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.50-16	14PR	H666	5.50F	740	140	630	1040
7.00-16	14PR	H666	5.50F	770	145	770	1330
7.50-16	14PR	H666	6.00G	805	160	770	1550
8.25-16	16PR	H666	6.50H	815	175	770	1850



H667 B

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.00-16	10PR	H667B	4.50B	730	170	530	750



H668 B

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.50-16	14PR	H668	5.50F	740	140	630	1040

H688

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.00-13	10PR	H688	4.50E	655	170	530	670
6.00-14	10PR	H688	4.50J	665	125	530	800
6.00-15	10PR	H688	4.50E	695	120	530	825
6.50-16	14PR	H688	5.50F	740	140	630	1040
7.00-16	14PR	H688	5.50F	770	145	770	1330
7.50-16	14PR	H688	6.00G	805	160	770	1550
8.25-16	16PR	H688	6.50H	815	175	770	1850



卡车胎

TRUCK TYRE

H669

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.00-16	14PR	H669	5.50F	770	145	770	1330
9.00-20	18PR	H669	7.0	1018	259	830	2600
10.00-20	18PR	H669	7.5	1055	278	840	2900
11.00-20	18PR	H669	8.0	1105	293	910	3650
12.00-20	18PR	H669	8.5	1145	315	795	3725



H686

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
7.50-16	14PR	H686	6.00G	805	160	770	1550

H687

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
6.50-16	14PR	H687	5.50F	740	140	630	1040
7.00-16	14PR	H687	5.50F	770	145	770	1330
7.50-16	14PR	H687	6.00G	805	160	770	1550



TRAILER TYRE

拖车胎

HC301 MOBILE HOME TIRE

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
8-14.5	16PR	HC301	6.00MH	706	203	420	1380



HC302

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	RIM	MAX LOAD(LBS)		PRSSURE(PSI)		LOAD RANGE
				SINGLE	DUAL	SINGLE	DUAL	
10.00-20	14PR	HC302	7.5	6175	5750	100	90	G
11-22.5	14PR	HC302	8.25	6175	5750	100	90	G



HC303

SIZE	PR	PATTERN CODE	LOAD IN KG MINIMUM	LOAD RANGE LOAD INDEX	OVERALL DIAMETER MM	SECTION WIDTH MM	MAX PSI LBS RATED
ST205/70D15	6PR	TRAILER	HC303	C	689	203	50
ST225/75D15	8PR	TRAILER	HC303	D	719	223	65
ST205/90D15 (ST7.00-15)	12PR	TRAILER	HC303	F	850	215	90
ST225/90D16 (ST7.50-16)	10PR	TRAILER	HC303	E	750	200	75



农机具轮胎

AGRICULTURAL IMPLEMENT TYRE

HC306

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
15.5/65-18	12PR	HC306	13	980	395	310	2890
16.5/70-18	14PR	HC306	5.00F	1065	425	410	3650



军用胎

MILITARY TYRE

E-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
1200X500-508	12PR	E-2	388-508	1200	500	500	4400
1300X530-533	16PR	E-2	440X533	1300	530	475	4500
18.00-24 (1600x500-610)	24PR	E-2	13.00	1600	500	530	8200
1500X600-635	14PR	E-2	500X635	1500	600	380	5750



E-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
1025x420-457	16PR	E-2	330-462	1025	420	650	3250



SAND TYRE

沙漠胎

SAND TYRE

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
14.00-20	18PR	SERIAL 1	10.00	1215	332	245	4125
14.00-20	18PR	SERIAL 2	10.00	1215	332	245	4125
14.00-20	18PR	SERIAL 3	10.00	1215	332	245	4125
16.00-20	18PR	SERIAL 4	10.00	1330	388	325	4350



SERIAL 1



SERIAL 2



SERIAL 3



SERIAL 4

FLOATATION TYRE

浮力胎

I-3

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
400/60-15.5	14PR	I-3	13*15.5	870	404	360	2900
500/60-22.5	16PR	I-3	16*22.5	1172	500	300	3875
550/45-22.5	14PR	I-3	16*22.5	1022	503	280	3350
550/60-22.5	16PR	I-3	16*22.5	1232	545	300	5450
600/50-22.5	16PR	I-3	20*22.5	1172	611	320	5600
600/55-22.5	16PR	I-3	20*22.5	1330	611	320	5600



林业异形胎

FOREST SPECIAL SIZED TYRE

LS-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
30.5L-32	26PR	LS-2	DH27	1845	775	280	7100



R-1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
66X43.00-25	16PR	R-1	36.00	1702	1054	290	6100



F-101

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
18-15.5	14PR	F-101	13.0	980	450	350	4185



GRASS MACHINERY TYRE

草地机械轮胎

GRASS MACHINERY TYRE PATTERN R-1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 Rim type	外直径 (mm) OVERALL DIAMETER	断面宽 (mm) SECTION WIDTH	标准气压 (kpa) RELEVANT PRESSURE	单胎负荷 (kg) MAX LOADING
26x12.00-12	8PR	R-1	10.5	648	307	140	810
31X15.5-15 (400/50-15)	8PR	R-1	13	792	391	310	1250



SELF-MADE MOLD

自制模具

